

ADG.2(A/S) Air die grinders



Watch our machines in action on:
www.youtube.com/euroboorbv

Technical data	ADG.2A	ADG.2S
Weight	0.53 kg	0.67 kg
Free speed	20,000 rpm	
Collet	6 mm	
Air inlet (PT)	1/4"	
Air hose (ID)	3/8"	
Avg. air consumption	0.113 m ³ /min (4 SCFM)	0.142 m ³ /min (5 SCFM)
Working pressure	6.3 bar (90 psi)	
Length	193 mm	
Height	70 mm	

Benefits

- Excellent for grinding, polishing, deburring and smoothing sharp edges
- Four-speed rear regulator
- 360 degrees adjustable exhaust deflector
- Safety lever trigger

Features



Adjustable
speed



Air motor:
min 6.3 bar
(90 PSI)

Available as

- Carton box
- Standard 6 mm (1/4") collet
- Optional 3 mm (1/8") collet

ADG.2A / ADG.2S

- Luxury case
- Standard 6 mm (1/4") and 3 mm (1/8") collet

ADG.2A-CASE / ADG.2S-CASE

- Luxury case set, including a 10 pieces rotary burrs set. Set includes:
 - Standard 6 mm (1/4") and 3 mm (1/8") collet
 - Rotary burrs type B cylinder with end cut (RB.B0606 + RB.B1206)
 - Rotary burrs type C cylinder ball nose (RB.C0606 + RB.C1206)
 - Rotary burrs type D cylinder ball (RB.D0606 + RB.D1206)
 - Rotary burrs type F cylinder ball nose tree (RB.F0606 + RB.F1206)
 - Rotary burrs type G cylinder arc pointed tree (RB.G0606 + RB.G1206)

ADG.2A-SET / ADG.2S-SET



ADG.2A



ADG.2S