

LASER LEVEL



- with a strong magnet in the milled surface
- laser wave-length is 670 nm
- the mounting tolerance of the horizontal vial is 0.25 mm/m
- laser ray range in rooms: 30 m
- protected against dust and moisture

| Prod. nr. | Prod. code | EAN code | Length (cm) | Packing |
|-----------|------------|---------------|-------------|---------|
| 1331339 | BLL035 | 3838853405959 | 35 | 1 |
| 1331330 | BLL080 | 3838853405942 | 80 | 1 |

TRIPOD



- made of light metal design, connecting thread 5/8 inch
- height can be changed with a simple stretching mechanism
- model BST242 is additionally provided with a crank lift for legs' stretching

| Prod. nr. | Prod. code | EAN code | Length (cm) | Packing |
|-----------|------------|---------------|-------------|---------|
| 1340209 | BST160 | 3838853214032 | 160 | 1 |
| 1340214 | BST242 | 3838853406208 | 242 | 1 |

LEVELLING PLATFORM



- heavy-weight metal design, rotating, bearing-supported
- the device can be used as a stand-alone unit on the floor or on a tripod (1/4, 3/8 and 5/8 inch thread)
- bull's-eye vial integrated in the rotation disc
- uncontrolled rotation avoided with an integrated brake

| Prod. nr. | Prod. code | EAN code | Packing |
|-----------|------------|---------------|---------|
| 1340205 | BVG | 3838853215510 | 1 |

LASER SET



- set in a carrying case (450 × 300 × 160 mm) includes a laser level with 35 cm length (BLL035), a levelling platform (BVG), a beam deflecting prism (BOP1) and laser spectacles (BOL)
- technical characteristics are the same as for single components

| Prod. nr. | Prod. code | EAN code | Packing |
|-----------|------------|---------------|---------|
| 1331411 | BLS | 3838853218108 | 1 |



BEAM DEFLECTING PRISM



- for deflection of a laser beam by 90° (model BOP1), with the possibility of 360° rotation
- model BOP2: deflection 50 % of laser power under angle 90°, and 50 % travel further in the direction of the basic ray without interruption

| Prod. nr. | Prod. code | EAN code | Packing |
|-----------|------------|---------------|---------|
| 1340220 | BOP1 | 3838853214575 | 1 |
| 1340219 | BOP2 | 3838853216142 | 1 |

LASER DISTANCE METRE - DISTO D5



- for accurate measurements, especially of larger distances on heavy approachable places, without additional assistance
- measuring is done quickly, exactly in the laser point that we see
- digital Pointfinder with 4 × zoom and high resolution color display
- Features like Trapezium function, Pythagorean functions, 45° Tilt sensor, Power Range Technology™
- it allows defining of three different starting measuring points (in front, behind, tripod)
- measuring accuracy +/- 1 mm, range 200 m
- also other models available

| Prod. nr. | Prod. code | EAN code | Packing |
|-----------|------------|---------------|---------|
| 1331345 | BD | 3838853413688 | 1 |

LASER SPECTACLES



- improve the visibility of laser rays in unfavourable light conditions

| Prod. nr. | Prod. code | EAN code | Packing |
|-----------|------------|---------------|---------|
| 1340221 | BOL | 3838853214568 | 1 |

LASER SELF-LEVELLING



- auto levelling 5 dot and lines laser is used for levelling and aligning inside
- levelling precision: line laser +/- 3.0 mm/10 m; horizontal accuracy of dot laser +/- 3.0 mm/10 m; vertical accuracy of dot laser – up +/- 1.5 mm/3 m; vertical accuracy of dot laser – down +/- 1.5 mm/2 m
- levelling: automatically in zone + / - 3°
- included in set: Automagic, magnetic multifunction base with connecting thread 1/4" and 5/8" for the tripod, target plate, battery, soft bag
- additional option BLM SET: BLM + electronic laser detector

| Prod. nr. | Prod. code | EAN code | Packing |
|-----------|------------|---------------|---------|
| 1331901 | BLM | 3838853414432 | 1 |
| 1331902 | BLM-SET | 3838853414449 | 1 |